

# Vfp SERIES

FINE PITCH FIXED INSTALLATION

## Models with Built-In Redundancy



PIXEL PITCH	0.94mm	1.25mm	1.56mm	1.87mm	2.5mm
MODEL NAME	Vfp0.9r	Vfp1.2r	Vfp1.5r	Vfp1.8r	Vfp2.5r
PIXELS PER CABINET	640 x 360 (230,400)	480 x 270 (129,600)	384 x 216 (82,944)	320 x 180 (57,600)	240 x 135 (32,400)
LED DRIVER IC	Chipone ICND2069	Chipone ICND2065	Chipone ICND2065	Chipone ICND2055	Macroblock MBI5253
RECEIVING CARD	(2x) NovaStar A10s Pro	(2x) NovaStar A8s	(2x) NovaStar A8s	(2x) NovaStar A8s	(2x) NovaStar A8s
CABINET SIZE	≥600 NITS	≥600 NITS	≥600 NITS	≥1200 NITS	≥1200 NITS
CABINET MATERIAL	600mm (W) / 337.5mm (H) / 40mm (D)		600mm (W) / 337.5mm (H) / 40mm (D)		
CABINET WEIGHT	Aluminum			Aluminum	
MODULE SIZE	12.76 lbs			12.76 lbs	
LED TYPE	150mm x 168.75mm			150mm x 168.75mm	
REFRESH RATE	Nationstar Gold Wire			Nationstar Gold Wire	
BRIGHTNESS	≥3840 Hz			≥3840 Hz	
GRAYSCALE	≥14 bits			≥14 bits	
VIEWING ANGLE	160° Horizontal & 160° Vertical			160° Horizontal & 160° Vertical	
SERVICE ACCESS	Front			Front	
CURVE	Yes - With Optional Brackets			Yes - With Optional Brackets	
IP RATING	IP30			IP30	
VOLTAGE RANGE	110-240 VAC 50-60Hz			110-240 VAC 50-60Hz	
AVG. POWER DRAW	.22A@208 / .41A@110	.20A@208 / .38A@110	.21A@208 / .39A@110	.20A@208 / .37A@110	.18A@208 / .34A@110
MAX POWER DRAW	.67A@208 / 1.26A@110	.65A@208 / 1.24A@110	.65A@208 / 1.23A@110	.63A@208 / 1.20A@110	.63A@208 / 1.18A@110