

Vfp SERIES

FINE PITCH FIXED INSTALLATION



PIXEL PITCH	0.94mm	1.25mm	1.56mm	1.87mm	2.5mm	
MODEL NAME	Vfp0.9	Vfp1.2	Vfp1.5	Vfp1.8	Vfp2.5	Vfp2.5
PIXELS PER CABINET	640 x 360 (230,400)	480 x 270 (129,600)	384 x 216 (82,944)	320 x 180 (57,600)	240 x 135 (32,400)	240 x 135 (32,400)
LED DRIVER IC	Chipone ICND2069	Chipone ICND2065	Chipone ICND2065	Chipone ICND2055	Macroblock MBI5253	Macroblock MBI5253
RECEIVING CARD	NovaStar A10s Pro	NovaStar A8s	NovaStar A8s	NovaStar A8s	NovaStar A8s	Brompton
BRIGHTNESS	≥600 NITS	≥600 NITS	≥600 NITS	≥600 NITS	≥1200 NITS	≥1200 NITS
CABINET SIZE	600mm (W) / 337.5mm (H) / 40mm (D)			600mm (W) / 337.5mm (H) / 40mm (D)		
CABINET MATERIAL	Aluminum			Aluminum		
CABINET WEIGHT	11.66 lbs			11.66 lbs		
MODULE SIZE	150mm x 168.75mm			150mm x 168.75mm		
LED TYPE	Nationstar Gold Wire			Nationstar Gold Wire		
REFRESH RATE	≥3840 Hz			≥3840 Hz		
GRayscale	≥14 bits			≥14 bits		
VIEWING ANGLE	160° Horizontal & 160° Vertical			160° Horizontal & 160° Vertical		
SERVICE ACCESS	Front			Front		
CURVE	Yes - With Optional Brackets			Yes - With Optional Brackets		
IP RATING	IP30			IP30		
VOLTAGE RANGE	100-240 VAC 50-60Hz			100-240 VAC 50-60Hz		
AVG. POWER DRAW	.21A@208 / .39A@110	.20A@208 / .37A@110	.20A@208 / .38A@110	.19A@208 / .35A@110	.17A@208 / .32A@110	.17A@208 / .32A@110
MAX POWER DRAW	.65A@208 / 1.23A@110	.63A@208 / 1.20A@110	.63A@208 / 1.18A@110	.62A@208 / 1.16A@110	.60A@208 / 1.14A@110	.60A@208 / 1.14A@110